

UPM Raflatac Technical Information

31.10.2013 ENG 847

SELF-ADHESIVE	ROLLS
FACE	JETCOLOR ON-DEMAND-FSC
A4 Papers	CJU (sales code)
Product	Special coated matt finished paper.
Use	Multicolour ink-jet printing, high resolution. Specially designed for on-demand industrial applications with improved drying time.

Typical technical values

Substance	88	g/m ²	ISO 536
Caliper	113	µm	ISO 534
Tensile strength MD	5.66	kN/m	ISO 1924/2
Tensile strength CD	3.33	kN/m	ISO 1924/2
Brightness	90	%	ISO 2470/1
Smoothness	67	Bekk sec	ISO 5627 min
Opacity	89	%	ISO 2471

Printability Inkjet printing, suitable for dye-based inks. Ink-jet coating has been specially designed for the purpose, and the characteristics of these coatings might compromise the print result when using conventional methods such as flexography and offset.

Sustainability The product named as FSC is registered to SGSCH-COC-004879 FSC™ Mix credit.

Disclaimer Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

